

# ELECTROMECHANICAL OPERATOR FOR SLIDING GATES

## LINCE

EN TESTED 24Vdc Encoder



Quiet in operation.  
Safety. Obstacle detection  
Without limit switches  
Smart. Self learning of the open/close travel and slow down  
distances  
LCD programming  
Option to work with batteries



 ERREKA



## LINCE KITS

### LINCE 1

Operator LIS424 (1 pc.)  
 Nylon rack N2112 (4 mts.)  
 Two button transmitter SOL2 (2 pcs.)  
 Receiver RTPSH250 (1 pc.)  
 Pair of photocells LECP (1 pc.)

### LINCE 5

Operator LIS824 (1 pc.)  
 Nylon rack N2122 (4 mts.)  
 Two button transmitter SOL2 (2 pcs.)  
 Receiver RTPSH250 (1 pc.)  
 Pair of photocells LECP (1 pc.)

### \_Other accesories

Keypads, electrolocks, flashing lamps,  
 rubber edges, magnetic loop metal  
 detectors, traffic lights,...



#### KIT LINCE 1



LIS424  
1 und.



N2112  
4 mts.



LECP  
1 und.



LUO2  
2 unds.



R RSD-SH  
1 und.

## TECHNICAL DATA

	LIS424	LIS824
Power supply	230 / 50 Vac/Hz Vcc	230 / 50 Vac/Hz Vcc
Motor voltage	24 Vdc	24 Vdc
Protection class	IP45	IP45
Torque max.	10 Nm	15 Nm
Operating temperature	-20 / +55 °C	-20 / +55 °C
Operator weight	9 kg	9 kg
Max Gate weight	400 kg	800 kg
Use	Intensif	Intensif

